

# NORBAR TORQUE TOOLS

## HYDRAULIC TORQUE WRENCH - NSD SERIES



MODEL	SQUARE DRIVE	RANGE		DIMENSIONS (mm)										WEIGHT (kg)
		N·m	lbf·ft	L1	L2	L3	H1	H2	W1	W2	W3	R	RA	
NSD-1	¾"	194 - 1,874	143 - 1,382	40	133	151	104	145	50	69	56	30	94	3.18
NSD-3	1"	355 - 3,960	262 - 2,921	47	183	202	124	166	70	91	81	32	136	6.35
NSD-6	1 ½"	765 - 6,928	564 - 5,110	55	193	214	151	199	76	114	89	44	139	9.53
NSD-8	1 ½"	1,150 - 11,585	848 - 8,545	52	175	227	172	214	99	136	122	46	165	14.06
NSD-11	1 ½"	1,407 - 14,633	1,038 - 10,793	57	222	239	187	232	99	136	127	52	127	16.33
NSD-20	2 ½"	2,377 - 24,315	1,753 - 17,934	88	264	295	233	274	126	189	141	76	191	34.02
NSD-30	2 ½"	3,577 - 34,986	2,638 - 25,804	88	276	298	248	289	149	213	141	79	191	41.28
NSD-45	2 ½"	5,966 - 63,223	4,400 - 46,631	186	318	338	285	320	146	210	140	83	189	68.04
NSD-60	2 ½"	6,932 - 74,441	5,113 - 54,905	150	373	406	356	396	184	248	146	95	223	134.26

